NSN 3040-00-084-1115

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-084-1115

| First End Outside Diameter: |
|--|
| 0.812 inches |
| Mounting Provision: |
| Unthreaded mounting holes |
| Tempurature Rating: |
| 400.0 degrees fahrenheit |
| Overall Width: |
| Between 4.980 inches and 5.020 inches |
| Body Outside Diameter: |
| Between 2.090 inches and 2.100 inches |
| Overall Diameter: |
| 2.500 inches |
| First End External Thread Length: |
| 3.250 inches |
| Compressed Length: |
| 20.075 inches |
| Extended Length: |
| 26.640 inches |
| Pressure Rating: |
| 3000.0 pounds per square inch |
| Integral Valve Operation Method: |
| Hydraulic |
| Design Characteristics: |
| Double acting single cylinder |
| First Piston Rod End Style: |
| External threaded |
| First Piston Rod End Thread Series Designator: |
| Unef |
| First Piston Rod End Thread Diameter: |
| 0.812 inches |
| First Piston Rod End Thready Qty Per Inch (tpi): |
| 20 |
| First Piston Rod End Thread Class: |
| 3a |
| Mounting Type And Location: |
| Lug cylinder head end |
| Mounting Facility Diameter: |
| 0.500 inches |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 3040-00-084-1115

Linear Actuating Cylinder Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A34200