NSN 3040-00-086-6781

Rigid Connecting Link - Page 1 of 1

Mil-std (military Standard):

Mil-s-7720 spec.



View Online at https://aerobasegroup.com/nsn/3040-00-086-6781 **Overall Length:** Between 6.581 inches and 6.601 inches **Body Diameter:** 0.312 inches Link Style: Solid shank **Body Construction:** Solid **End Attachment Style:** В1 **End Attachment Hole Diameter:** 0.2496 inches both ends **End Attachment Length:** 1.992 inches second end **End Attachment Width:** 0.655 inches first end **Special Features:** Surface treatment: passivated bps fw4007 bell helicopter co or cadmium plated, qq-p-416 class 2 type 2; effective length: 5.400 to 5.600 inches; link threading length and size: right hand, 3.980 to 4.020 inches, 5/15-24 nf; end attachment info: material steel, comp 4130 or 4340, surface treatment cadmium plated, locknut, rockwell c 32.0 to 36.0, second end attachment distance from center to flats 0.500 inch with flatsat 14 degrees both sides of vertical centerline Material: Steel **Material Specification:** Mil-s-7720 comp 303se/s or mil-s-6758 comp 4130 cond d4 military specification 1st material response **Surface Treatment:** Passivate or cadmium Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli Fiig: A524I0