## NSN 3040-00-091-6849

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-091-6849 First End Style: Splined (involute) **End Similarity:** Not identical Second End Style: Splined (involute) **Overall Length:** 1.875 inches First End Diameter: 0.5010 inches First End Spline Length: 0.672 inches First End Spline Minor Diameter: Between 0.5260 inches and 0.5360 inches First End Spline Major Diameter: Between 0.6430 inches and 0.6500 inches First End Pressure Angle: 30.0000 degrees First End Pitch Diameter: 0.6000 inches **Second End Diameter:** 0.5310 inches **Second End Spline Length:** Between 0.812 inches and 0.826 inches **Second End Spline Minor Diameter:** Between 0.5260 inches and 0.5360 inches **Second End Spline Major Diameter:** Between 0.6430 inches and 0.6500 inches **Second End Pressure Angle:** 30.0000 degrees **Second End Pitch Diameter:** 0.6000 inches **Step Quantity:** First End Spline Quantity: **Second End Spline Quantity:** 12 **Largest Step Diameter:** 

0.750 inches **Surface Finish:** 

32.0 microinches

## NSN 3040-00-091-6849

Shouldered Shaft - Page 2 of 2



М	at	er	ia	ŀ
•••	u	٠.	···	••

Beryllium copper

## **Material Specification:**

Spec 250, fscm 62983 mfr ref single material response

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A23200