## NSN 3040-00-125-7892

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-125-7892
Thread Class:
2a both ends
Thread Direction:
Right-hand both ends
Thread Length:
0.340 inches both ends
Overall Length:
35.188 inches
Wrenching Facility Outside Diameter:
1.000 inches both ends
Tip Length:
0.500 inches both ends
Shank Outside Diameter:
0.500 inches both ends
Core Material:
Steel
Screw Thread Series Designator:
Uns both ends
Core Diameter:
0.150 inches
Thread Location:
Internal both ends
End Type:
Round keyed both ends
End Connection Type:
Threaded internal both ends
Setscrew:
Not included both ends
Casing Material:
Steel
Wrenching Facility Type:
Knurled surface both ends
Cross Section Size And Location:
0.187 inches diameter both ends
Casing Surface Treatment:
Zinc coated

**Casing Length Between Ferrules:** 

34.313 inches

**Casing Outside Diameter:** 

0.445 inches

**Casing Protective Device Type:** 

Not w/cover, shield, or protector

## NSN 3040-00-125-7892

Flexible Shaft Assembly - Page 2 of 2



Swivel End:
Not provided both ends
Enddiameter:
0.875 inches both ends
Lubrication Fitting:
Not provided both ends
Corelength:
35.188 inches
Core Rotation Direction:
Clockwise
Core Removability:
Removable
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T246-e