NSN 3040-00-135-6535

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-135-6535

First End Style:

Circular grooved and splined (straight)

First End Groove Width:

Between 0.0560 inches and 0.0600 inches

First End Groove Diameter:

Between 1.3060 inches and 1.3140 inches

End Similarity:

Not identical

Second End Style:

Woodruff keyway and internally threaded

Overall Length:

10.375 inches

First End Distance From End To Groove:

Between 2.065 inches and 2.069 inches

First End Diameter:

Between 1.3781 inches and 1.3785 inches

First End Spline Length:

2.125 inches

First End Spline Minor Diameter:

Between 1.1760 inches and 1.1800 inches

First End Spline Major Diameter:

Between 1.3700 inches and 1.3720 inches

Second End Keyway Width:

Between 0.3760 inches and 0.3780 inches

Second End External Keyway Length:

1.467 inches

Second End Distance From Keyway Center To End:

0.812 inches

Second End Diameter:

Between 1.5749 inches and 1.5753 inches

Second End Internal Thread Length:

0.750 inches

Step Quantity:

5

First End Spline Quantity:

10

Largest Step Diameter:

1.750 inches

Surface Finish:

63.0 microinches

Material:

Steel comp 4140 or steel comp 4142 or steel comp 4145

NSN 3040-00-135-6535

Shouldered Shaft - Page 2 of 2



М	ater	ial	Sp	ecifi	icati	on:

Qq-s-624 federal specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23200