## NSN 3040-00-143-5345



Shouldered Shaft - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3040-00-143-5345 First End Style: Flat keyway **End Similarity:** Not identical Second End Style: Splined (involute) **Overall Length:** Between 2.183 inches and 2.193 inches First End Keyway Width: Between 0.0580 inches and 0.0595 inches First End External Keyway Length: 0.313 inches First End Keyway Depth: 0.071 inches First End Diameter: Between 0.1610 inches and 0.1690 inches **Second End Diameter:** Between 0.4335 inches and 0.4345 inches Second End Spline Length: Between 0.151 inches and 0.161 inches **Second End Spline Minor Diameter:** Between 0.4075 inches and 0.4095 inches **Second End Spline Major Diameter:** Between 0.4335 inches and 0.4345 inches **Second End Pressure Angle:** 40.0 degrees **Second End Pitch Diameter:** Between 0.4190 inches and 0.4210 inches Step Quantity: 4 **Second End Spline Quantity:** 

#### **Largest Step Diameter:**

Between 0.590 inches and 0.592 inches

Material:

Steel

### **Material Specification:**

Ams6330 assn standard single material response or ams6320 assn standard single material response or ams6322 assn standard single material response or 9-2901 mfr ref single material response

Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 3040-00-143-5345

Shouldered Shaft - Page 2 of 2



Demilitarization:

No

Fiig:

A23200