NSN 3040-00-150-1933

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-150-1933

Body Materia	l:
--------------	----

Aluminum alloy, ams4212 or aluminum alloy, ams4260

First End Outside Diameter:

0.5620 inches and 0.5625 inches all working ends

Inside Diameter:

0.097 inches all ports

Mounting Provision:

Unthreaded mounting holes

Tempurature Rating:

Not rated

Bore Diameter:

Between 0.344 inches and 1.501 inches

End Application:

T-55 series engines

Seat Angle In Deg:

37.0 all ports

First End Hole Diameter:

0.1895 inches and 0.1900 inches all working ends

First End Thickness At Mounting Holes:

0.276 inches and 0.281 inches all working ends

Pressure Rating:

Not rated

Design Characteristics:

Single acting single cylinder

First Piston Rod End Style:

Bearing type all working ends

Mounting Type And Location:

Lug center section

Mounting Facility Diameter:

Between 0.279 inches and 0.284 inches

Port Location And Quantity:

2 center section and 1 cylinder head end

Port Style:

Plain 1st port

Port Thread Series Designator:

Unf single port

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 3040-00-150-1933

Linear Actuating Cylinder Assembly - Page 2 of 2



Fiig:

A34200