## NSN 3040-00-157-3650



Shouldered Shaft - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3040-00-157-3650 First End Style: Circular grooved First End Groove Width: 0.1870 inches First End Groove Diameter: Between 2.5530 inches and 2.5630 inches **End Similarity:** Not identical Second End Style: Unthreaded cross drilled **Overall Length:** Between 7.440 inches and 7.480 inches First End Distance From End To Groove: 0.493 inches First End Diameter: Between 2.7732 inches and 2.7738 inches **Second End Diameter:** Between 1.9362 inches and 1.9368 inches **Second End Hole Diameter:** 0.1250 inches **Second End Distance From Hole Center To End:** 2.038 inches **Second End Hole Depth:** 0.968 inches Step Quantity: 5 **Largest Step Diameter:** Between 2.770 inches and 2.774 inches **Surface Finish:** 50.0 microinches **Special Features:** First end longitudinal drill hole: 0.500in. Diameter 1.827 in. Maximum depth threaded 1.477 in. Min thd depth 0.500-20unf-2b; second end longitudinal drill hole 0.3025 in. Min 0.3225 in. Maximum dia. 2.200 in. Min 2.250 in. Maximum depth Material: Steel comp 8625 **Material Specification:** Qq-s-624 federal specification all material responses Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## **NSN 3040-00-157-3650** Shouldered Shaft - Page 2 of 2



Fiig:

A23200