NSN 3040-00-157-5087

A524I0

Mil-s-7720 spec.

Mil-std (military Standard):



Rigid Connecting Link - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/3040-00-157-5087 **Overall Length:** Between 6.501 inches and 6.521 inches **Body Diameter:** 0.312 inches Link Style: Solid shank **Body Construction:** Solid **End Attachment Style:** В1 **End Attachment Hole Diameter:** 0.2496 inches both ends **End Attachment Length:** 1.992 inches second end **End Attachment Width:** 0.655 inches first end **Special Features:** Surface treatment passivated bps fw4007 bell helicopter co or cadmium plated qq-p-416 cl2 ty2; effective length: 5.400 to 5.440 inches; link threading length and size: right hand, 3.700 to 3.740 inches, 5/16-24 nf; end attachment info: material steel, comp 4130 ro 4340, surface treatment cadmium plated, rockwell c 32.0 to 36.0, locknut, diameter 1.000 to 1.173 inches, second end attachment distance from center to flats 0.500 inch with flatsat 14 deg. Both sides of vertical centerline Material: Steel **Material Specification:** Mil-s-7720 comp 303se/s or mil-s-6758 comp 4130 cond d4 military specification 1st material response **Surface Treatment:** Passivate or cadmium Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli Fiig: