

View Online at <https://aerobasegroup.com/nsn/3040-00-157-5087>

Overall Length:

Between 6.501 inches and 6.521 inches

Body Diameter:

0.312 inches

Link Style:

Solid shank

Body Construction:

Solid

End Attachment Style:

B1

End Attachment Hole Diameter:

0.2496 inches both ends

End Attachment Length:

1.992 inches second end

End Attachment Width:

0.655 inches first end

Special Features:

Surface treatment passivated bps fw4007 bell helicopter co or cadmium plated qq-p-416 cl2 ty2; effective length: 5.400 to 5.440 inches; link threading length and size: right hand, 3.700 to 3.740 inches, 5/16-24 nf; end attachment info: material steel, comp 4130 ro 4340, surface treatment cadmium plated, rockwell c 32.0 to 36.0, locknut, diameter 1.000 to 1.173 inches, second end attachment distance from center to flats 0.500 inch with flats at 14 deg. Both sides of vertical centerline

Material:

Steel

Material Specification:

Mil-s-7720 comp 303se/s or mil-s-6758 comp 4130 cond d4 military specification 1st material response

Surface Treatment:

Passivate or cadmium

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A52410

Mil-std (military Standard):

Mil-s-7720 spec.