## NSN 3040-00-167-2456

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-167-2456

## First End Outside Diameter:

1.875 inches all working ends

**Mounting Provision:** 

Unthreaded mounting holes

**Tempurature Rating:** 

Not rated

**Overall Height:** 

5.000 inches

**Overall Width:** 

8.500 inches

**Longest Horizontal Distance Between Mounting Centers:** 

78.500 inches

**Longest Vertical Distance Between Mounting Centers:** 

**6.750** inches

First End External Thread Length:

3.000 inches all working ends

Compressed Length:

85.500 inches

**Mounting Provision Arrangement Style:** 

Four hole rectangular

**Pressure Rating:** 

Not rated

**Integral Valve Operation Method:** 

Hydraulic

**Design Characteristics:** 

Single acting single cylinder

First Piston Rod End Style:

External threaded all working ends

First Piston Rod End Thread Series Designator:

Uni all working ends

First Piston Rod End Thread Diameter:

1.875 inches all working ends

First Piston Rod End Thready Qty Per Inch (tpi):

12 all working ends

**Mounting Type And Location:** 

Lug cylinder head end and lug piston rod end

**Mounting Facility Diameter:** 

1.062 inches

**Port Location And Quantity:** 

1 cylinder head end and 1 piston rod end

Port Style:

Gasket seal all ports

## NSN 3040-00-167-2456

Linear Actuating Cylinder Assembly - Page 2 of 2



Port Thread Series Designator:
Unf all ports
Port Thread Diameter:
0.750 inches all ports
Port Thready Qty Per Inch (tpi):
16 all ports
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A34200