NSN 3040-00-167-2491

Body Material:

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-167-2491

Steel, aisi c1015
Mounting Provision:
Unthreaded mounting holes
Tempurature Rating:
Not rated
Overall Height:
5.000 inches
Overall Width:
8.500 inches
Bore Diameter:
4.000 inches
Longest Horizontal Distance Between Mounting Centers:
84.000 inches
Longest Vertical Distance Between Mounting Centers:
6.750 inches
First End Hole Diameter:
2.002 inches and 2.005 inches all working ends
Compressed Length:
95.688 inches
Mounting Provision Arrangement Style:
Four hole rectangular
Pressure Rating:
3000.0 pounds per square inch
Features Provided:
Cushioned stroke
Integral Valve Operation Method:
Hydraulic
Design Characteristics:
Single acting single cylinder
First Piston Rod End Style:
Fork type (clevis) all working ends
First End Fork Width:
4.000 inches all working ends
First End Fork Depth:
4.500 inches all working ends
First End Fork Span Width:
2.500 inches all working ends
Mounting Type And Location:
Lug cylinder head end and lug piston rod end
Mounting Facility Diameter:
1.062 inches

NSN 3040-00-167-2491

Linear Actuating Cylinder Assembly - Page 2 of 2



Port Location And Quantity: 1 cylinder head end and 1 piston rod end Port Style: Gasket seal all ports Port Thread Series Designator: Un all ports Port Thread Diameter: 0.750 inches all ports Port Thready Qty Per Inch (tpi): 12 all ports Shelf Life: N/a Unit Of Measure: --

Demilitarization:

No Fiig: A34200