NSN 3040-00-167-2491

Body Material:

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-167-2491

| Steel, aisi c1015 |
|---|
| Mounting Provision: |
| Unthreaded mounting holes |
| Tempurature Rating: |
| Not rated |
| Overall Height: |
| 5.000 inches |
| Overall Width: |
| 8.500 inches |
| Bore Diameter: |
| 4.000 inches |
| Longest Horizontal Distance Between Mounting Centers: |
| 84.000 inches |
| Longest Vertical Distance Between Mounting Centers: |
| 6.750 inches |
| First End Hole Diameter: |
| 2.002 inches and 2.005 inches all working ends |
| Compressed Length: |
| 95.688 inches |
| Mounting Provision Arrangement Style: |
| Four hole rectangular |
| Pressure Rating: |
| 3000.0 pounds per square inch |
| Features Provided: |
| Cushioned stroke |
| Integral Valve Operation Method: |
| Hydraulic |
| Design Characteristics: |
| Single acting single cylinder |
| First Piston Rod End Style: |
| Fork type (clevis) all working ends |
| First End Fork Width: |
| 4.000 inches all working ends |
| First End Fork Depth: |
| 4.500 inches all working ends |
| First End Fork Span Width: |
| 2.500 inches all working ends |
| Mounting Type And Location: |
| Lug cylinder head end and lug piston rod end |
| Mounting Facility Diameter: |
| 1.062 inches |

NSN 3040-00-167-2491

Linear Actuating Cylinder Assembly - Page 2 of 2



Port Location And Quantity: 1 cylinder head end and 1 piston rod end Port Style: Gasket seal all ports Port Thread Series Designator: Un all ports Port Thread Diameter: 0.750 inches all ports Port Thready Qty Per Inch (tpi): 12 all ports Shelf Life: N/a Unit Of Measure: --

Demilitarization:

No Fiig: A34200