## NSN 3040-00-167-2711

Shouldered Shaft - Page 1 of 2

First End Style:

6

View Online at https://aerobasegroup.com/nsn/3040-00-167-2711



## Circular grooved First End Groove Width: 0.0890 inches First End Groove Diameter: Between 0.9150 inches and 0.9210 inches **End Similarity:** Not identical Second End Style: Circular grooved flat keyway and externally threaded Second End Groove Width: Between 0.0550 inches and 0.0680 inches Second End Groove Diameter: Between 0.9460 inches and 0.9480 inches **Overall Length:** Between 5.610 inches and 5.670 inches First End Distance From End To Groove: 0.075 inches First End Diameter: Between 0.9842 inches and 0.9846 inches Second End Distance From End To Groove: 0.418 inches Second End Keyway Width: 0.1800 inches Second End External Keyway Length: 0.605 inches Second End Keyway Depth: 0.089 inches Second End Diameter: 0.9690 inches Second End External Thread Length: 0.418 inches **Step Quantity:** Largest Step Diameter: Between 1.4995 inches and 1.4997 inches Surface Finish: 32.0 microinches Material: Stainless steel **Material Specification:**

Aisi 416 assn standard single material response or qq-s-764, type 416, cond a federal specification single material response

## NSN 3040-00-167-2711

Shouldered Shaft - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23200

