## NSN 3040-00-169-0723

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-169-0723

View Online at https://aerobasegroup.com/nsn/3040-00-169-0723
First End Style:
Circular grooved and externally threaded
First End Groove Width:
0.1500 inches
First End Groove Diameter:
Between 0.2310 inches and 0.2410 inches
End Similarity:
Not identical
Second End Style:
Circular grooved flat keyway and externally threaded
Second End Groove Width:
0.1500 inches
Second End Groove Diameter:
Between 0.4170 inches and 0.4270 inches
Overall Length:
21.520 inches
End Application:
NHA1-68-000-0801
First End Distance From End To Groove:
0.850 inches
First End Diameter:
0.3125 inches
First End External Thread Length:
0.850 inches
Second End Distance From End To Groove:
1.100 inches
Second End External Keyway Length:
1.750 inches
Second End Diameter:
0.5000 inches
Second End External Thread Length:
1.100 inches
Step Quantity:
5
Largest Step Diameter:
0.500 inches
Surface Finish:
125.0 microinches
Special Features:
Two 0.160 in. Diameter by 0.090 in. Deep holes, 8.330 in. And 9.500 in. From first end

Material:

Steel comp 17-4ph

## NSN 3040-00-169-0723

Shouldered Shaft - Page 2 of 2



Material Specification
------------------------

Ams-5643 assn standard single material response

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A23200