## NSN 3040-00-169-4913

Shouldered Shaft - Page 1 of 2

Cross drilled and externally threaded

Woodruff keyway and cross drilled

First End Style:

End Similarity: Not identical

Second End Style:

Overall Length: 19.875 inches

0.7500 inches

First End Diameter:



View Online at https://aerobasegroup.com/nsn/3040-00-169-4913

First End Hole Diameter:						
0.1880 inches						
First End Distance From Hole Center To End:						
0.188 inches						
First End External Thread Length:						
0.782 inches						
First End Hole Depth:						
0.750 inches						
Second End Keyway Width:						
0.3120 inches						
Second End External Keyway Length:						
1.135 inches						
Second End Distance From Keyway Center To End:						
4.437 inches						
Second End Diameter:						
Between 1.8745 inches and 1.8750 inches						
Second End Hole Diameter:						
0.3125 inches						
Second End Distance From Hole Center To End:						
1.066 inches						
Second End Hole Depth:						
Between 1.8745 inches and 1.8750 inches						
Step Quantity:						
17						
Largest Step Diameter:						
2.625 inches						
Surface Finish:						
63.0 microinches						
Special Features:						
Second end, two additional, identical woodruff keyways; space keyways 120 degrees apart						
Material:						
Steel, carbon, 1040 through 1048						

## NSN 3040-00-169-4913

Shouldered Shaft - Page 2 of 2



M	late	rial	Sp	ecif	icat	ion:
			~	••••		. •

Qq-s634 federal specification single material response

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A23200