## NSN 3040-00-186-8224

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-186-8224

First End Style: Splined (straight) **End Similarity:** Not identical Second End Style: Splined (straight) **Overall Length:** Between 2.430 inches and 2.440 inches **End Application:** Starter, engine, gas turbine p/n 383242-1-8, 383934-1-2; usaf type stu-20/a34; u/o j79-ge-15 First End Diameter: Between 0.9550 inches and 0.9650 inches First End Spline Length: Between 0.580 inches and 0.610 inches First End Spline Minor Diameter: Between 0.9760 inches and 0.9860 inches First End Spline Major Diameter: Between 1.0950 inches and 1.1000 inches **Second End Diameter:** Between 1.0950 inches and 1.1000 inches **Second End Spline Length:** Between 0.570 inches and 0.600 inches **Second End Spline Minor Diameter:** Between 1.0850 inches and 1.0950 inches **Second End Spline Major Diameter:** Between 1.2620 inches and 1.2670 inches Step Quantity: First End Spline Quantity: 21 **Second End Spline Quantity: Largest Step Diameter:** Between 1.117 inches and 1.121 inches **Surface Finish:** 63.0 microinches Material: Steel **Material Specification:** Mil-s-5000 military specification single material response Shelf Life:

N/a

## NSN 3040-00-186-8224

Shouldered Shaft - Page 2 of 2



Unit Of Mea	sure:
-------------	-------

--

Demilitarization:

No

Fiig:

A23200

Mil-std (military Standard):

Mil-s-5000 spec.