NSN 3040-00-215-1344

Body Material: Aluminum alloy

Inside Diameter:

0.250 inches all ports

Mounting Provision:

Second End Outside Diameter: 1.000 inches all working ends

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-215-1344

Unthreaded mounting holes
Overall Height:
7.000 inches
Overall Width:
10.000 inches
Bore Diameter:
0.625 inches
Body Outside Diameter:
1.750 inches
Longest Horizontal Distance Between Mounting Centers:
1.875 inches
Longest Vertical Distance Between Mounting Centers:
1.000 inches
End Application:
Truck, fire fighting, type 0-11a
First End Hole Diameter:
0.312 inches all working ends
Second End Hole Diameter:
0.312 inches all working ends
First End Thickness At Mounting Holes:
0.312 inches all working ends
Second End Thickness At Mounting Holes:
0.437 inches all working ends
Compressed Length:
13.000 inches
Extended Length:
15.000 inches
Mounting Provision Arrangement Style:
Four hole rectangular
First End Tongue Length:
1.125 inches all working ends
Integral Valve Operation Method:
Hydraulic
Design Characteristics:

Double acting tandem cylinder

NSN 3040-00-215-1344 Linear Actuating Cylinder Assembly - Page 2 of 2



First Piston Rod End Style:
Tongue type all working ends
Piston Rod End Similarity:
Not identical
Second Piston Rod End Style:
Bearing type
First End Fork Width:
0.562 inches all working ends
Mounting Type And Location:
Flange piston rod end
Mounting Facility Diameter:
0.250 inches
Port Location And Quantity:
4 center section and 2 cylinder head end and 2 piston rod end
Port Style:
Plain all ports
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A34200