

NSN 3040-00-216-6518 Flexible Shaft Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3040-00-216-6518 **Thread Class:** 2b both ends **Thread Direction:** Right-hand both ends **Overall Length:** 10.625 inches **Wrenching Facility Outside Diameter:** 1.000 inches both ends **Thread Depth:** 0.375 inches both ends Tip Length: 1.875 inches both ends **Core Material:** Steel **Screw Thread Series Designator:** Uns both ends **Core Surface Treatment:** Copper plated **Core Diameter:** 0.188 inches **Thread Location:** Internal both ends **End Type:** Round keyed both ends **End Connection Type:** Union ferrule both ends **Casing Material:** 

Steel

**Wrenching Facility Type:** 

Serrated surface both ends

**Cross Section Size And Location:** 

0.188 inches diameter both ends

**Machined Feature Size:** 

0.060 in.W x 0.281 in.Long x 0.037 in.H

**Casing Surface Treatment:** 

Cadmium

**Casing Length Between Ferrules:** 

5.812 inches

**Casing Outside Diameter:** 

0.375 inches

Swivel End:

Not provided both ends

## NSN 3040-00-216-6518

Flexible Shaft Assembly - Page 2 of 2



| Overall End Size:                            |
|--|
| Both ends: 0.812 in. Diameter x 1.438 in. Lg |
| Lubrication Fitting:                         |
| Not provided both ends                       |
| Corelength:                                  |
| 8.250 inches                                 |
| Core Rotation Direction:                     |
| Clockwise                                    |
| Core Removability:                           |
| Removable                                    |
| Shelf Life:                                  |
| N/a  |
| Unit Of Measure:                             |
|  |
| Demilitarization:                            |
| No   |

Fiig: T246-e