## NSN 3040-00-225-1442

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-225-1442

First End Style:
Slotted
End Similarity:
Not identical
Second End Style:
Two cross drilled holes and externally threaded
Overall Length:
3.969 inches
First End Slot Width:
0.250 inches
First End Diameter:
1.1800 inches
First End Slot Depth:
0.156 inches
Second End Diameter:
0.5000 inches
Second End Hole Diameter:
Between 0.1250 inches and 0.1520 inches
Second End Distance From Hole Center To End:
0.187 inches
Second End External Thread Length:
0.407 inches
Second End Hole Depth:
0.500 inches
Second End Distance Between Hole Centers:
0.700 inches
Second End Angle Between Holes:
90.0 degrees
Step Quantity:
5
Largest Step Diameter:
1.180 inches
Surface Finish:
63.0 microinches
Special Features:
3/8 in. Diameter hole 2 5/8 in. Deep 1st end, c'bored 1/2 in. Diameter by 1 1/8 in. Deep; groove 0.010 in. Wide shaft center
Material:
Steel comp 4130
Material Specification:
Astm-a304 assn standard single material response or mil-s-6758 cond f military specification single material response
Shelf Life:

N/a

## NSN 3040-00-225-1442

Shouldered Shaft - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A23200

Mil-std (military Standard):

Mil-s-6758 spec.