NSN 3040-00-225-1443

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-225-1443

First End Style: Three circular grooves First End Groove Width: Between 0.0950 inches and 0.0970 inches First End Groove Diameter: Between 0.9740 inches and 0.9940 inches **End Similarity:** Not identical Second End Style: Two circular grooves, splined and internally threaded Second End Groove Width: 0.1750 inches Second End Groove Diameter: 0.9062 inches **Overall Length:** 6.375 inches First End Distance From End To Groove: 0.085 inches First End Diameter: Between 1.1100 inches and 1.1200 inches First End Distance Between First And Second Groove Centers: 0.247 inches First End Distance Between Second And Third Groove Centers: 0.257 inches Second End Distance From End To Groove: 0.5938 inches Second End Diameter: Between 1.2495 inches and 1.2500 inches Second End Spline Length: 0.594 inches Second End Spline Minor Diameter: Between 0.9630 inches and 0.9730 inches Second End Spline Major Diameter: Between 1.1230 inches and 1.1240 inches Second End Internal Thread Length: 1.000 inches Second End Distance Between First And Second Groove Centers: 0.762 inches **Step Quantity:** 15 Second End Spline Quantity: 10

NSN 3040-00-225-1443

Shouldered Shaft - Page 2 of 2



Largest Step Diameter:

1.400 inches

Surface Finish:

125.0 microinches

Material:

Steel comp 1018 or steel comp 1117

Material Specification:

Astm a108 assn standard 1st material response or qq-s-637 federal specification 2nd material response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A23200