NSN 3040-00-230-3708

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-230-3708

| First End Style: |
|--|
| Plain |
| End Similarity: |
| Not identical |
| Second End Style: |
| Splined (involute) |
| Overall Length: |
| 6.500 inches |
| First End Diameter: |
| Between 0.7480 inches and 0.7520 inches |
| Second End Diameter: |
| Between 0.7866 inches and 0.7869 inches |
| Second End Spline Length: |
| 1.480 inches |
| Second End Spline Minor Diameter: |
| Between 0.5497 inches and 0.5627 inches |
| Second End Spline Major Diameter: |
| 0.7268 inches |
| Second End Pressure Angle: |
| 30.0 degrees |
| Second End Pitch Diameter: |
| 0.6667 inches |
| Step Quantity: |
| 3 |
| Second End Spline Quantity: |
| 8 |
| Largest Step Diameter: |
| 0.786 inches |
| Surface Finish: |
| 125.0 microinches |
| Material: |
| Steel |
| Material Specification: |
| Mil-s-6758 military specification single material response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A23200 |
| |

NSN 3040-00-230-3708

Shouldered Shaft - Page 2 of 2

Mil-std (military Standard):

Mil-s-6758 spec.

