## NSN 3040-00-249-7086



Shouldered Shaft - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3040-00-249-7086 First End Style: Unthreaded cross drilled **End Similarity:** Not identical **Second End Style:** Two cross drilled holes **Overall Length:** 4.090 inches **End Application:** Aircraft, galaxy c-5 **First End Diameter:** 0.8120 inches First End Hole Diameter: Between 0.1710 inches and 0.1810 inches First End Distance From Hole Center To End: 0.310 inches **Second End Diameter:** Between 1.0605 inches and 1.0615 inches **Second End Hole Diameter:** Between 0.3775 inches and 0.3785 inches **Second End Distance From Hole Center To End:** 0.560 inches **Second End Distance Between Hole Centers:** 0.500 inches **Second End Angle Between Holes:** 90.0 degrees Step Quantity: **Largest Step Diameter:** Between 1.0605 inches and 1.0615 inches **Surface Finish:** 32.0 microinches **Special Features:** 1st end has 0.750 in. Dia. Bore. 2nd end has internal involute splines. Critical technology Material: Steel **Material Specification:** Ams 6260, comp 9310 assn standard single material response Shelf Life: N/a

**Unit Of Measure:** 

## NSN 3040-00-249-7086

Shouldered Shaft - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A23200