## NSN 3040-00-287-9168

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-287-9168

First End Style:

Circular grooved woodruff keyway and externally threaded

First End Groove Width:

0.0950 inches

First End Groove Diameter:

0.4400 inches

**End Similarity:** 

Not identical

Second End Style:

Circular grooved and splined (straight)

**Second End Groove Diameter:** 

Between 0.4450 inches and 0.4550 inches

**Overall Length:** 

7.293 inches

**End Application:** 

Bell model uh-1n helicopter

First End Distance From End To Groove:

0.548 inches

First End Keyway Width:

Between 0.1240 inches and 0.1250 inches

First End External Keyway Length:

0.875 inches

First End Distance From Keyway Center To End:

1.126 inches

First End Diameter:

Between 0.5015 inches and 0.5030 inches

First End External Thread Length:

0.500 inches

**Second End Distance From End To Groove:** 

0.400 inches

**Second End Diameter:** 

Between 0.9346 inches and 0.9365 inches

**Second End Spline Length:** 

0.400 inches

**Second End Spline Minor Diameter:** 

Between 0.6826 inches and 0.6926 inches

**Second End Spline Major Diameter:** 

Between 0.8450 inches and 0.8500 inches

Step Quantity:

a

**Second End Spline Quantity:** 

16

## NSN 3040-00-287-9168

Shouldered Shaft - Page 2 of 2



Largest Step Diameter:
Between 0.973 inches and 0.975 inches
Surface Finish:
32.0 microinches
Material:
Steel comp 4340
Material Specification:
Aisi4340 assn standard single material response
Fsc Application Data:
Fan, ventilating
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

**Fiig:** A23200