NSN 3040-00-301-7431

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-301-7431

First End Style: Flat keyway **End Similarity:** Not identical Second End Style: Circular grooved and flat keyway **Second End Groove Width:** 0.0630 inches **Second End Groove Diameter:** 0.9840 inches **Overall Length:** 22.250 inches First End Keyway Width: Between 0.5000 inches and 0.5040 inches First End External Keyway Length: Between 3.219 inches and 3.281 inches First End Keyway Depth: Any acceptable First End Diameter: Between 1.9995 inches and 2.0000 inches First End Hole Depth: Between 0.276 inches and 0.290 inches **Second End Distance From End To Groove:** 3.687 inches Second End Keyway Width: Between 0.2500 inches and 0.2580 inches Second End External Keyway Length: Between 2.219 inches and 2.281 inches Second End Keyway Depth: Any acceptable **Second End Diameter:** Between 0.9995 inches and 1.0000 inches Second End Hole Depth: Between 0.135 inches and 0.149 inches **Step Quantity: Largest Step Diameter:** Between 1.9995 inches and 2.0000 inches **Surface Finish:** 8.0 microinches **Special Features:**

Distance between groove center 1.031 in. Nom

NSN 3040-00-301-7431 Shouldered Shaft - Page 2 of 2



Material:
Steel comp 6150
Material Specification:
Aisi or sae assn standard single material response
Fsc Application Data:
Hydraulic pump, winch, vehicle mounted
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A23200