NSN 3040-00-319-2239

Flexible Shaft Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3040-00-319-2239

 8.000 inches End Connection Type: Plain ferrule both ends Casing Material: Copper-nickel alloy Torsional Deflection Rating: 0.5 degrees per inlb ninding and 0.5 degrees per inlb unwinding torsional deflection Casing Length Between Ferrules: 5.688 inches Casing Outside Diameter: 0.156 inches
 Plain ferrule both ends Casing Material: Copper-nickel alloy Torsional Deflection Rating: 0.5 degrees per inlb ninding and 0.5 degrees per inlb unwinding torsional deflection Casing Length Between Ferrules: 5.688 inches Casing Outside Diameter:
Casing Material: Copper-nickel alloy Torsional Deflection Rating: 0.5 degrees per inlb ninding and 0.5 degrees per inlb unwinding torsional deflection Casing Length Between Ferrules: 5.688 inches Casing Outside Diameter:
Copper-nickel alloy Torsional Deflection Rating: 0.5 degrees per inlb ninding and 0.5 degrees per inlb unwinding torsional deflection Casing Length Between Ferrules: 5.688 inches Casing Outside Diameter:
Torsional Deflection Rating: 0.5 degrees per inlb ninding and 0.5 degrees per inlb unwinding torsional deflection Casing Length Between Ferrules: 5.688 inches Casing Outside Diameter:
 0.5 degrees per inlb ninding and 0.5 degrees per inlb unwinding torsional deflection Casing Length Between Ferrules: 5.688 inches Casing Outside Diameter:
Casing Length Between Ferrules: 5.688 inches Casing Outside Diameter:
5.688 inches Casing Outside Diameter:
Casing Outside Diameter:
-
0.156 inches
Casing Protective Device Type:
Plastic cover
Enddiameter:
0.185 inches both ends
Minimum Operating Radius:
2.250 inches
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Т246-е