NSN 3040-00-321-8730

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-321-8730 First End Style: Tongue **End Similarity:** Not identical Second End Style: Flat keyways and internally threaded **Overall Length:** Between 5.033 inches and 5.043 inches First End Tongue Thickness: Between 0.3095 inches and 0.3105 inches First End Tongue Width: Between 0.806 inches and 0.807 inches First End Diameter: Between 0.8060 inches and 0.8070 inches **Second End Keyway Width:** Between 0.1250 inches and 0.1260 inches Second End External Keyway Length: Between 1.635 inches and 1.650 inches Second End Keyway Depth: Between 0.064 inches and 0.074 inches Second End Diameter: Between 0.6855 inches and 0.6860 inches Second End Internal Thread Length: 0.625 inches Step Quantity: **Largest Step Diameter:** 0.807 inches First End Step Length: 0.312 inches **Surface Finish:** 32.0 microinches Material: Steel or steel comp 3140 or steel comp 8740 **Material Specification:** Qq-s-624, fs3135 federal specification 1st material response or qq-s-624 federal specification 2nd material response or qq-s-624 federal specification 3rd material response **Fsc Application Data:** Pump, fuel injection, engine, except aircraft and guided missile prime moving

Unit Of Measure:

N/a

Shelf Life:

NSN 3040-00-321-8730

Shouldered Shaft - Page 2 of 2



Demilitarization:

No

Fiig:

A23200