NSN 3040-00-350-9200

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-350-9200 **Body Material:** Steel First End Outside Diameter: 0.250 inches **Bore Diameter:** 0.500 inches **Body Outside Diameter:** 1.000 inches Seat Angle In Deg: 37.0 **Mounting Facility Thread Class:** 2a **Mounting Facility Thread Direction:** Right-hand First End External Thread Length: 0.375 inches **Compressed Length:** 3.370 inches **Extended Length:** 6.500 inches **Mounting Facility Circle Diameter:** 0.719 inches **Pressure Rating:** 5000.0 pounds per square inch **Mounting Facility Thread Series Designator:** Unc **Mounting Facility Thread Diameter:** 0.138 inches Mounting Facility Thready Qty Per Inch (tpi): 32 **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Unf First Piston Rod End Thread Diameter:

First Piston Rod End Thready Qty Per Inch (tpi):

28

0.250 inches

NSN 3040-00-350-9200

Linear Actuating Cylinder Assembly - Page 2 of 2



First Piston Rod End Thread Class:
2a
First Piston Rod End Thread Direction:
Right-hand
Mounting Type And Location:
Face mtg both ends abdrdal3bbbwl28
Mounting Facility Thread Length:
0.250 inches
Port Location And Quantity:
2 center section
Port Style:
Inverted flare
Port Thread Series Designator:
Unf
Port Thread Diameter:
0.438 inches
Port Thready Qty Per Inch (tpi):
20
Port Thread Class:
2a
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A34200