

View Online at <https://aerobasegroup.com/nsn/3040-00-355-1421>

Overall Length:

15.500 inches

Teeth Hardness Rating:

Between 56.0 rockwell c and 62.0 rockwell c

Worm Thread Quantity:

1

Worm Thread Lead:

0.500 inches

Worm Thread Direction:

Right-hand

Worm Pressure Angle In Deg:

20.000

Worm Helix Angle:

4 degrees 33 min

Worm Outside Diameter:

2.3155 inches

Worm Pitch Diameter:

2.000 inches

Shaft Hardness Rating:

Between 56.0 rockwell c and 62.0 rockwell c

Worm Thread Section Length:

2.625 inches

Worm Body Length:

4.096 inches

Worm Body Tapered Bearing Surface End:

Provided

Tapered Bearing Surface Largest Diameter:

1.3605 inches

Tapered Bearing Surface Smallest Diameter:

1.1545 inches

Tapered Bearing Surface Length:

0.4055 inches

Shaft Location:

One end of worm

Straight Unthreaded Length:

7.447 inches first end, first portion

Straight Unthreaded Section Diameter:

1.000 inches first end, second portion

Unthreaded Section Keyway Width:

0.2505 inches first end, second portion

Unthreaded Section Keyway Depth:

0.334 inches first end, second portion

Unthreaded Section Pin Hole Diameter:

0.2520 inches first end, second portion

Material:

Steel, qq-s-624, fs5120

Material:

Steel, qq-s-624, fs5120

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-c