## NSN 3040-00-369-3343

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-369-3343
Thread Class:
2a first end
Thread Direction:
Right-hand first end
Thread Length:
0.250 inches first end
Overall Length:
181.750 inches
Flange Thickness:
0.031 inches both ends
Tip Length:
0.875 inches first end
Shank Outside Diameter:
0.500 inches both ends
Shoulder Outside Diameter:
0.562 inches both ends
Core Material:
Steel
Screw Thread Series Designator:
Unef first end
Core Surface Treatment:
Any acceptable
Core Diameter:
0.156 inches
Thread Location:
External first end
End Type:
Threaded female second end
End Connection Type:
Threaded external first end
Casing Material:
Steel
Cross Section Size And Location:
0.094 inches across flats second end
Casing Surface Treatment:
Any acceptable
Casing Length Between Ferrules:

176.000 inches

**Casing Outside Diameter:** 

0.438 inches

**Casing Protective Device Type:** 

Plastic cover

## **NSN 3040-00-369-3343**Flexible Shaft Assembly - Page 2 of 2



Swivel End:
Not provided both ends
Enddiameter:
0.875 inches second end
Overall End Size:
First end: 1.000 in. Across flats, hexagon
Lubrication Fitting:
Not provided both ends
Corelength:
181.000 inches
Core Rotation Direction:
Counterclockwise
Core Removability:
Nonremovable
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T246-e