## NSN 3040-00-369-3343

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-369-3343

Thread Class:         2a first end         Thread Direction:         Right-hand first end         Oze50 inches first end         Ozerall Length:         181.750 inches         Flange Thickness:         0.031 inches both ends         Tip Length:         0.875 inches first end         Shank Outside Diameter:         0.800 inches both ends         Shoulder Outside Diameter:         0.500 inches both ends         Core Material:         Steel         Core Material:         Steel         Core Surface Treatment:         Any acceptable         Core Jameter:         0.156 inches         Thread Length:         Thread Length:         Outside Diameter:         0.156 inches         Thread Series Designator:         Unef first end         Core Jamete:         0.156 inches         Thread Location:         External first end         End Type:         Threaded female second end         End Secton Size And Location:         0.094 inches across flats second end         Casing Material:         Sheel         <	
Thread Direction:         Right-hand first end         Thread Length:         0.250 inches first end         Overall Length:         181.750 inches         Flange Thickness:         0.031 inches both ends         Tip Length:         0.875 inches first end         Shank Outside Diameter:         0.800 inches both ends         Shoulder Outside Diameter:         0.502 inches both ends         Shoulder Outside Diameter:         0.502 inches both ends         Core Material:         Steel         Screw Thread Series Designator:         Unef first end         Core Surface Treatment:         Any acceptable         Core Diameter:         0.156 inches         Thread Centon:         External first end         External first end         End Type:         Threaded female second end         Casing Material:         Steel         Cose Section Size And Location:         0.094 inches across flats second end         Casing Surface Treatment:         Any acceptable         Casing Surface Treatment:         Any acceptable         Casing Surface Treatment: </th <th></th>	
Right-hand first end         Thread Length:         0.250 inches first end         Overall Length:         181.750 inches         Flange Thickness:         0.031 inches both ends         Tip Length:         0.875 inches first end         Shank Outside Diameter:         0.500 inches both ends         Shoulder Outside Diameter:         0.500 inches both ends         Shoulder Outside Diameter:         0.500 inches both ends         Shoulder Outside Diameter:         0.500 inches both ends         Steel         Steel         Steel         Core Material:         Nay acceptable         Core Surface Treatment:         Any acceptable         Core Jameter:         0.156 inches         Thread Location:         External first end         End Type:         Threaded second end         End Steei         Cross Section Size And Location:         0.094 inches across flats second end         Casing Materia!         Any acceptable         Cross Section Size And Location:         0.094 inches across flats second end         Casing Lungth Between Ferrules: </th <th></th>	
Thread Length:         0.250 inches first end         Overall Length:         181.750 inches         Flange Thickness:         0.031 inches both ends         Tp Length:         0.875 inches first end         Shank Outside Diameter:         0.500 inches both ends         Shoulder Outside Diameter:         0.502 inches both ends         Shoulder Outside Diameter:         0.502 inches both ends         Core Material:         Steel         Steel         Stered         Core Surface Treatment:         Any acceptable         Core Jameter:         0.156 inches         Thread Location:         External first end         End Type:         Threaded female second end         Endrype:         Threaded female second end         Casing Material:         Steel         Core Section Size And Location:         0.094 inches across flats second end         Casing Material:         Nay acceptable         Cross Section Size And Location:         0.094 inches across flats second end         Casing Length Between Ferrules:         176.000 inches	
0.250 inches0verall Length:181.750 inchesFlange Thickness:0.031 inches both endsTip Length:0.875 inches first endShank Outside Diameter:0.500 inches both endsShoulder Outside Diameter:0.552 inches both endsCore Material:SteelScrew Thread Series Designator:Unef first endCore Surface Treatment:Any acceptableCore Jameter:0.156 inchesThread Location:External first endEnd Type:Threaded female second endEnd Type:SteelConsection Type:Threaded setmanl first endCasing Material:SteelCross Section Size And Location:0.094 inches across flats second endCasing Surface Treatment:Any acceptableCasing Length Between Ferrules:176.000 inchesCasing Outside Diameter:0.438 inchesCasing Protective Device Type:	-
Overall Length:181.750 inchesFlange Thickness:0.031 inches both endsTip Length:0.875 inches first endShank Outside Diameter:0.500 inches both endsShoulder Outside Diameter:0.562 inches both endsCore Material:SteelStrew Thread Series Designator:Unef first endCore Surface Treatment:Any acceptableCore Diameter:0.156 inchesThread Location:External first endEnd Type:Threaded female second endEnd Type:Onse Section Size And Location:0.094 inches across flats second endCasing Material:Any acceptableCores Section Size And Location:0.094 inchesAny acceptableCasing Surface Treatment:Any acceptableCasing Surface Treatment:Any acceptableCasing Material:SteelCross Section Size And Location:Any acceptableCasing Surface Treatment:Any acceptableCasing Length Between Ferrules:Any acceptableCasing Length Between Ferrules:Any acceptableCasing Length Between Ferrules:Any acceptableCasing Outside Diameter:0.438 inchesCasing Protective Device Type:	Thread Length:
181.750 inches         0.031 inches both ends <b>Tip Length:</b> 0.875 inches first end <b>Shank Outside Diameter:</b> 0.500 inches both ends <b>Shoulder Outside Diameter:</b> 0.562 inches both ends <b>Core Material:</b> Steel <b>Screw Thread Series Designator:</b> Unef first end <b>Core Surface Treatment:</b> Any acceptable <b>Core Diameter:</b> 0.156 inches <b>Thread Location:</b> External first end <b>End Type:</b> Threaded female second end <b>End Type:</b> Threaded female second end <b>End Connection Type:</b> Threaded sternal first end <b>Cross Section Size And Location:</b> 0.094 inches across flats second end <b>Casing Surface Treatment:</b> Any acceptable <b>Casing Surface Treatment:</b> Any acceptable <b>Casing Length Between Ferrules:</b> Any acceptable <b>Casing Length Between Ferrules:</b> Any acceptable <b>Casing Length Between Ferrules:</b> 176.000 inches <b></b>	0.250 inches first end
Flange Thickness:         0.031 inches both ends         Tip Length:         0.875 inches first end         Shank Outside Diameter:         0.500 inches both ends         Shoulder Outside Diameter:         0.562 inches both ends         Shoulder Outside Diameter:         0.562 inches both ends         Core Material:         Steel         Screw Thread Series Designator:         Unef first end         Core Surface Treatment:         Any acceptable         Core Diameter:         0.156 inches         Thread Location:         External first end         End Type:         Threaded female second end         End Connection Type:         Threaded female second end         Casing Material:         Steel         Cross Section Size And Location:         0.094 inches across flats second end         Casing Surface Treatment:         Any acceptable         Casing Surface Treatment:         Any acceptable         Casing Length Between Ferrules:         Any acceptable         Casing Length Between Ferrules:         Arya acceptable         Casing Outside Diameter:	Overall Length:
No. 1No. 2No. 3No. 3Sinches first endShank Outside Diameter:0.500 inches both endsShoulder Outside Diameter:0.562 inches both endsCore Material:SteelScrew Thread Series Designator:Unef first endCore Surface Treatment:Any acceptableCore Diameter:0.156 inchesThread Location:External first endEnd Type:Threaded female second endEnd Type:Threaded sternal first endCasing Material:SteelCros Section Size And Location:0.094 inches across flats second endCasing Surface Treatment:Any acceptableCasing Length Between Ferrules:Arie Surg Outside Diameter:Arie Surg Outside Diameter:Casing Outside Diameter:Casing Outside Diameter:Casing Outside Diameter:Casing Outside Diameter:Casing Outside Diameter:	181.750 inches
Tip Length:         0.875 inches first end         Shank Outside Diameter:         0.500 inches both ends         Shoulder Outside Diameter:         0.562 inches both ends         Core Material:         Steel         Screw Thread Series Designator:         Unef first end         Core Surface Treatment:         Any acceptable         Core Diameter:         0.156 inches         Thread Location:         External first end         End Type:         Threaded female second end         End Type:         Threaded sternal first end         Casing Material:         Steel         Cross Section Size And Location:         0.094 inches across flats second end         Casing Surface Treatment:         Any acceptable         Casing Surface Treatment:         Any acceptable         Casing Surface Treatment:         Any acceptable         Casing Length Between Ferrules:         Any acceptable         Casing Outside Diameter:         Any acceptable         Casing Custide Diameter:         Any acceptable         Casing Outside Diameter:         Anyal inches	Flange Thickness:
0.875 inches first end Shank Outside Diameter: 0.500 inches both ends Shoulder Outside Diameter: 0.562 inches both ends Core Material: Steel Screw Thread Series Designator: Unef first end Core Surface Treatment: Any acceptable Core Diameter: 0.156 inches Thread Location: External first end External first end End Type: Threaded female second end End Type: Threaded female second end End Connection Type: Threaded sternal first end Casing Material: Steel Cross Section Size And Location: 0.094 inches across flats second end Casing Surface Treatment: Any acceptable Casing Length Between Ferrules: 176.000 inches Casing Outside Diameter: 0.438 inches	0.031 inches both ends
Shank Outside Diameter:0.500 inches both endsShoulder Outside Diameter:0.562 inches both endsCore Material:SteelScrew Thread Series Designator:Unef first endCore Surface Treatment:Any acceptableCore Diameter:0.156 inchesThread Location:External first endEnd Type:Threaded female second endEnd Connection Type:Threaded second endCasing Material:SteelCores Section Size And Location:0.094 inches across flats second endCasing Surface Treatment:Any acceptableCasing Length Between Ferrules:176.000 inchesCasing Outside Diameter:0.438 inchesCasing Protective Device Type:	Tip Length:
0.500 inches both ends Shoulder Outside Diameter: 0.562 inches both ends Core Material: Steel Screw Thread Series Designator: Unef first end Core Surface Treatment: Any acceptable Core Diameter: 0.156 inches Thread Location: External first end End Type: Threaded female second end End Type: Threaded female second end End Connection Type: Threaded external first end Casing Material: Steel Cross Section Size And Location: 0.094 inches across flats second end Casing Surface Treatment: Any acceptable Casing Length Between Ferrules: 176.000 inches Casing Outside Diameter: 0.438 inches	0.875 inches first end
Shoulder Outside Diameter:         0.562 inches both ends         Core Material:         Steel         Screw Thread Series Designator:         Unef first end         Core Surface Treatment:         Any acceptable         Core Diameter:         0.156 inches         Thread Location:         External first end         End Type:         Threaded female second end         End Connection Type:         Threaded sternal first end         Casing Material:         Steel         Cross Section Size And Location:         0.094 inches across flats second end         Casing Surface Treatment:         Any acceptable         Casing Length Between Ferrules:         176.000 inches         Casing Outside Diameter:         0.438 inches         Casing Protective Device Type:	Shank Outside Diameter:
0.562 inches both ends Core Material: Steel Screw Thread Series Designator: Unef first end Core Surface Treatment: Any acceptable Core Diameter: 0.156 inches Thread Location: External first end End Type: Threaded female second end End Connection Type: Threaded female second end End Connection Type: Threaded external first end Casing Material: Steel Cross Section Size And Location: 0.094 inches across flats second end Casing Surface Treatment: Any acceptable Casing Length Between Ferrules: 176.000 inches Casing Outside Diameter: 0.438 inches	0.500 inches both ends
Core Material:SteelScrew Thread Series Designator:Unef first endCore Surface Treatment:Any acceptableCore Diameter:0.156 inchesThread Location:External first endEnd Type:Threaded female second endEnd Connection Type:Threaded external first endCasing Material:SteelCross Section Size And Location:0.094 inches across flats second endCasing Surface Treatment:Any acceptableCasing Length Between Ferrules:176.000 inchesCasing Outside Diameter:0.438 inchesCasing Protective Device Type:	Shoulder Outside Diameter:
Steel Screw Thread Series Designator: Unef first end Core Surface Treatment: Any acceptable Core Diameter: 0.156 inches Thread Location: External first end End Type: Threaded female second end End Connection Type: Threaded external first end Casing Material: Steel Cross Section Size And Location: 0.094 inches across flats second end Casing Surface Treatment: Any acceptable Casing Length Between Ferrules: 176.000 inches Casing Outside Diameter: 0.438 inches	0.562 inches both ends
Screw Thread Series Designator: Unef first end Core Surface Treatment: Any acceptable Core Diameter: 0.156 inches Thread Location: External first end End Type: Threaded female second end End Connection Type: Threaded female second end Casing Material: Steel Cross Section Size And Location: 0.094 inches across flats second end Casing Surface Treatment: Any acceptable Casing Length Between Ferrules: 176.000 inches Casing Outside Diameter: 0.438 inches	Core Material:
Unef first endCore Surface Treatment:Any acceptableCore Diameter:0.156 inchesThread Location:External first endEnd Type:Threaded female second endEnd Connection Type:Threaded external first endCasing Material:SteelCross Section Size And Location:0.094 inches across flats second endCasing Surface Treatment:Any acceptableCasing Length Between Ferrules:176.000 inchesCasing Outside Diameter:0.438 inchesCasing Protective Device Type:	Steel
Core Surface Treatment: Any acceptable Core Diameter: 0.156 inches Thread Location: External first end End Type: Threaded female second end End Connection Type: Threaded external first end Casing Material: Steel Cross Section Size And Location: 0.094 inches across flats second end Casing Surface Treatment: Any acceptable Casing Length Between Ferrules: 176.000 inches Casing Outside Diameter: 0.438 inches	Screw Thread Series Designator:
Any acceptableCore Diameter:0.156 inchesThread Location:External first endEnd Type:Threaded female second endEnd Connection Type:Threaded external first endCasing Material:SteelCross Section Size And Location:0.094 inches across flats second endCasing Surface Treatment:Any acceptableCasing Length Between Ferrules:176.000 inchesCasing Outside Diameter:0.438 inchesCasing Protective Device Type:	Unef first end
Core Diameter:0.156 inchesThread Location:External first endEnd Type:Threaded female second endEnd Connection Type:Threaded external first endCasing Material:SteelCross Section Size And Location:0.094 inches across flats second endCasing Surface Treatment:Any acceptableCasing Length Between Ferrules:176.000 inchesCasing Outside Diameter:0.438 inchesCasing Protective Device Type:	Core Surface Treatment:
0.156 inches Thread Location: External first end End Type: Threaded female second end End Connection Type: Threaded external first end Casing Material: Steel Cross Section Size And Location: 0.094 inches across flats second end Casing Surface Treatment: Any acceptable Casing Length Between Ferrules: 176.000 inches Casing Outside Diameter: 0.438 inches	Any acceptable
Thread Location:External first endEnd Type:Threaded female second endEnd Connection Type:Threaded external first endCasing Material:SteelCross Section Size And Location:0.094 inches across flats second endCasing Surface Treatment:Any acceptableCasing Length Between Ferrules:176.000 inchesCasing Outside Diameter:0.438 inchesCasing Protective Device Type:	Core Diameter:
External first end End Type: Threaded female second end End Connection Type: Threaded external first end Casing Material: Steel Cross Section Size And Location: 0.094 inches across flats second end Casing Surface Treatment: Any acceptable Casing Length Between Ferrules: 176.000 inches Casing Outside Diameter: 0.438 inches Casing Protective Device Type:	0.156 inches
End Type:Threaded female second endEnd Connection Type:Threaded external first endCasing Material:SteelCross Section Size And Location:0.094 inches across flats second endCasing Surface Treatment:Any acceptableCasing Length Between Ferrules:176.000 inchesCasing Outside Diameter:0.438 inchesCasing Protective Device Type:	Thread Location:
Threaded female second endEnd Connection Type:Threaded external first endCasing Material:SteelCross Section Size And Location:0.094 inches across flats second endCasing Surface Treatment:Any acceptableCasing Length Between Ferrules:176.000 inchesCasing Outside Diameter:0.438 inchesCasing Protective Device Type:	External first end
End Connection Type:Threaded external first endCasing Material:SteelCross Section Size And Location:0.094 inches across flats second endCasing Surface Treatment:Any acceptableCasing Length Between Ferrules:176.000 inchesCasing Outside Diameter:0.438 inchesCasing Protective Device Type:	End Type:
Threaded external first end Casing Material: Steel Cross Section Size And Location: 0.094 inches across flats second end Casing Surface Treatment: Any acceptable Casing Length Between Ferrules: 176.000 inches Casing Outside Diameter: 0.438 inches Casing Protective Device Type:	Threaded female second end
Casing Material:SteelCross Section Size And Location:0.094 inches across flats second endCasing Surface Treatment:Any acceptableCasing Length Between Ferrules:176.000 inchesCasing Outside Diameter:0.438 inchesCasing Protective Device Type:	End Connection Type:
Steel Cross Section Size And Location: 0.094 inches across flats second end Casing Surface Treatment: Any acceptable Casing Length Between Ferrules: 176.000 inches Casing Outside Diameter: 0.438 inches Casing Protective Device Type:	Threaded external first end
Cross Section Size And Location: 0.094 inches across flats second end Casing Surface Treatment: Any acceptable Casing Length Between Ferrules: 176.000 inches Casing Outside Diameter: 0.438 inches Casing Protective Device Type:	Casing Material:
0.094 inches across flats second end Casing Surface Treatment: Any acceptable Casing Length Between Ferrules: 176.000 inches Casing Outside Diameter: 0.438 inches Casing Protective Device Type:	Steel
Casing Surface Treatment: Any acceptable Casing Length Between Ferrules: 176.000 inches Casing Outside Diameter: 0.438 inches Casing Protective Device Type:	Cross Section Size And Location:
Any acceptable Casing Length Between Ferrules: 176.000 inches Casing Outside Diameter: 0.438 inches Casing Protective Device Type:	0.094 inches across flats second end
Casing Length Between Ferrules: 176.000 inches Casing Outside Diameter: 0.438 inches Casing Protective Device Type:	Casing Surface Treatment:
176.000 inches Casing Outside Diameter: 0.438 inches Casing Protective Device Type:	Any acceptable
Casing Outside Diameter: 0.438 inches Casing Protective Device Type:	Casing Length Between Ferrules:
0.438 inches Casing Protective Device Type:	176.000 inches
Casing Protective Device Type:	Casing Outside Diameter:
	0.438 inches
Plastic cover	Casing Protective Device Type:
	Plastic cover

## NSN 3040-00-369-3343

Flexible Shaft Assembly - Page 2 of 2



Swivel End: Not provided both ends Enddiameter: 0.875 inches second end **Overall End Size:** First end: 1.000 in. Across flats, hexagon Lubrication Fitting: Not provided both ends Corelength: 181.000 inches **Core Rotation Direction:** Counterclockwise **Core Removability:** Nonremovable Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: T246-e