NSN 3040-00-382-1983



Flexible Shaft Assembly - Page 1 of 2	AUI
View Online at https://aerobasegroup.com/nsn/3040-00-382-1983	
Thread Class:	
3a both ends	
Thread Direction:	
Right-hand both ends	
Overall Length:	
Between 10.970 inches and 11.010 inches	
Wrenching Facility Outside Diameter:	
1.300 inches and 1.310 inches first end	
Thread Depth:	
0.590 inches and 0.600 inches second end	
Tip Length:	
0.860 inches both ends	
Core Material:	
Steel	
Screw Thread Series Designator:	
Uns both ends	
Core Diameter:	
0.250 inches	
Thread Location:	
Internal both ends	
End Type:	
Square male both ends	
End Connection Type:	
Threaded internal both ends	
Setscrew:	
Not included both ends	
Casing Material:	
Steel	

Wrenching Facility Type:

Knurled surface both ends

Bearing Type:

Sleeve both ends

Cross Section Size And Location:

0.310 inches diameter second end

Torsional Deflection Rating:

11 degrees ft-lb in.

Casing Surface Treatment:

Zinc coated or cadmium

Casing Length Between Ferrules:

7.150 inches

Casing Outside Diameter:

0.560 inches

NSN 3040-00-382-1983Flexible Shaft Assembly - Page 2 of 2



Swivel End:
Not provided both ends
Enddiameter:
1.300 inches and 1.310 inches first end
Lubrication Fitting:
Not provided both ends
Corelength:
Between 10.970 inches and 11.010 inches
Core Rotation Direction:
Clockwise
Core Removability:
Removable
Minimum Operating Radius:
4.250 inches
Fsc Application Data:
Window wiper mk3, mod 1, 3 and 4
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T246-e