

View Online at <https://aerobasegroup.com/nsn/3040-00-382-1984>

Thread Class:

3a both ends

Thread Direction:

Right-hand both ends

Overall Length:

Between 21.095 inches and 21.135 inches

Wrenching Facility Outside Diameter:

1.310 inches both ends

Thread Depth:

0.590 inches both ends

Tip Length:

0.840 inches and 0.860 inches both ends

Core Material:

Steel

Screw Thread Series Designator:

Uns both ends

Core Diameter:

0.250 inches

Thread Location:

Internal both ends

End Type:

Square male both ends

End Connection Type:

Threaded internal both ends

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Knurled surface both ends

Bearing Type:

Sleeve both ends

Cross Section Size And Location:

0.310 inches across flats both ends

Torsional Deflection Rating:

11 degrees ft-lb in.

Casing Surface Treatment:

Zinc coated or cadmium

Casing Length Between Ferrules:

19.215 inches

Casing Outside Diameter:

0.560 inches

Swivel End:

Not provided both ends

Enddiameter:

1.300 inches and 1.310 inches both ends

Lubrication Fitting:

Not provided both ends

Corelength:

Between 21.095 inches and 21.135 inches

Core Rotation Direction:

Clockwise or counterclockwise

Core Removability:

Removable

Minimum Operating Radius:

4.250 inches

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T246-e