NSN 3040-00-392-6249

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-392-6249

Thread Class:
3a both ends
Thread Direction:
Right-hand both ends
Overall Length:
7.376 inches
Wrenching Facility Outside Diameter:
0.625 inches both ends
Thread Depth:
0.250 inches both ends
Tip Length:
0.500 inches both ends
Shank Outside Diameter:
0.303 inches both ends
Core Material:
Bronze
Screw Thread Series Designator:
Unf both ends
Core Diameter:
0.130 inches
Thread Location:
Internal both ends
End Type:
Round, slotted external both ends
End Connection Type:
Threaded internal both ends
Setscrew:
Not included both ends
Casing Material:
Bronze
Wrenching Facility Type:
Knurled surface both ends
Cross Section Size And Location:
0.250 inches diameter both ends
Machined Feature Size:
0.078 by 0.406 in. Lg
Torsional Deflection Rating:
19 degrees ft-lb in. Torsional in winding direction and 30 degrees ft-lb in. Torsional rating in unwinding direction
Casing Length Between Ferrules:
5.750 inches
Casing Outside Diameter:
0.238 inches

NSN 3040-00-392-6249

Flexible Shaft Assembly - Page 2 of 2



Swivel End:
Not provided both ends
Enddiameter:
0.625 inches both ends
Lubrication Fitting:
Not provided both ends
Corelength:
7.376 inches
Core Rotation Direction:
Clockwise or counterclockwise
Core Removability:
Nonremovable
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T246-e