

View Online at <https://aerobasegroup.com/nsn/3040-00-400-0330>

**First End Style:**

Circular grooved

**First End Groove Width:**

Between 0.6562 inches and 0.6567 inches

**End Similarity:**

Not identical

**Second End Style:**

Splined (straight)

**Overall Length:**

7.320 inches

**First End Distance From End To Groove:**

1.190 inches

**First End Spline Length:**

2.330 inches

**First End Spline Minor Diameter:**

Between 0.7315 inches and 0.7398 inches

**First End Spline Major Diameter:**

Between 0.7972 inches and 0.8022 inches

**First End Hole Diameter:**

Between 0.2100 inches and 0.2200 inches

**First End Distance From Hole Center To End:**

Between 0.182 inches and 0.192 inches

**First End External Thread Length:**

Between 0.620 inches and 0.680 inches

**Second End Spline Length:**

1.085 inches

**Second End Spline Minor Diameter:**

Between 0.7318 inches and 0.7398 inches

**Second End Spline Major Diameter:**

Between 0.7972 inches and 0.8022 inches

**Second End Hole Diameter:**

Between 0.2100 inches and 0.2200 inches

**Second End Distance From Hole Center To End:**

Between 0.182 inches and 0.192 inches

**Second End External Thread Length:**

Between 0.620 inches and 0.680 inches

**Largest Step Diameter:**

Between 1.040 inches and 1.070 inches

**Surface Finish:**

32.0 microinches

**Material:**

Steel

**Material Specification:**

Mil-s-6709 military specification single material response

**Fsc Application Data:**

Actuator, leading edge slat, acft

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A23200

**Mil-std (military Standard):**

Mil-s-6709 spec.