## NSN 3040-00-406-4844

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-406-4844 First End Style: External threaded **End Similarity:** Not identical Second End Style: Circular grooved and slotted **Second End Groove Width:** Between 0.0290 inches and 0.0320 inches **Second End Groove Diameter:** Between 0.2290 inches and 0.2310 inches **Overall Length:** 1.560 inches Second End Slot Width: 0.046 inches First End Diameter: Between 0.4530 inches and 0.4580 inches First End External Thread Length: 0.380 inches **Second End Distance From End To Groove:** Between 0.007 inches and 0.009 inches **Second End Diameter:** Between 0.2496 inches and 0.2498 inches **Second End Slot Depth:** 0.040 inches Step Quantity: **Largest Step Diameter:** 0.560 inches Surface Finish: 32.0 microinches **Special Features:** Shaft is eccentric Material: Steel comp 303 **Material Specification:** Mil-s-7720, cond a military specification single material response Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 3040-00-406-4844

Shouldered Shaft - Page 2 of 2



Fiig:

A23200

Mil-std (military Standard):

Mil-s-7720 spec.