NSN 3040-00-450-7288

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-450-7288

First End Style:

Woodruff keyway

End Similarity:

Not identical

Second End Style:

Woodruff keyway and circular grooved

Second End Groove Width:

Between 0.0390 inches and 0.0420 inches

Second End Groove Diameter:

Between 0.4660 inches and 0.4700 inches

Overall Length:

3.600 inches

First End Distance From End To Groove:

0.093 inches

First End Keyway Width:

Between 0.1240 inches and 0.1250 inches

First End External Keyway Length:

0.500 inches

First End Distance From Keyway Center To End:

0.660 inches

First End Diameter:

Between 0.4993 inches and 0.4998 inches

Second End Distance From End To Groove:

0.083 inches

Second End Keyway Width:

Between 0.1240 inches and 0.1250 inches

Second End External Keyway Length:

0.500 inches

Second End Distance From Keyway Center To End:

0.690 inches

Second End Diameter:

Between 0.4998 inches and 0.5000 inches

Step Quantity:

3

Largest Step Diameter:

0.620 inches

Special Features:

Woodruff key first end, 0.124 in.W, 0.156 in. Dp, 0.500 in. Dia, 0.690 in. From keyway center to end

Material:

Steel comp 4140 or steel comp 4340

Material Specification:

Qq-s-624 federal specification single material response

NSN 3040-00-450-7288

Shouldered Shaft - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23200