NSN 3040-00-451-6681

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-451-6681

First End Style:

Circular grooved and splined (straight)

First End Groove Width:

Between 0.1030 inches and 0.1080 inches

First End Groove Diameter:

Between 3.0700 inches and 3.0820 inches

End Similarity:

Not identical

Second End Style:

Circular grooved and splined (straight)

Second End Groove Width:

Between 0.1030 inches and 0.1080 inches

Second End Groove Diameter:

Between 3.0700 inches and 3.0820 inches

Overall Length:

24.891 inches

First End Distance From End To Groove:

Between 2.728 inches and 2.738 inches

First End Diameter:

Between 3.3475 inches and 3.3484 inches

First End Spline Length:

1.538 inches

First End Spline Minor Diameter:

Between 3.0510 inches and 3.0620 inches

First End Spline Major Diameter:

Between 3.2450 inches and 3.2500 inches

Second End Distance From End To Groove:

2.958 inches

Second End Diameter:

Between 3.3475 inches and 3.3484 inches

Second End Spline Length:

1.868 inches

Second End Spline Minor Diameter:

Between 3.0510 inches and 3.0620 inches

Second End Spline Major Diameter:

Between 3.2450 inches and 3.2500 inches

Step Quantity:

9

First End Spline Quantity:

51

Second End Spline Quantity:

51

NSN 3040-00-451-6681

Shouldered Shaft - Page 2 of 2

Fiig: A23200



Largest Step Diameter:
Between 4.058 inches and 4.063 inches
Surface Finish:
63.0 microinches
Special Features:
2 external splines both 64 teeth, 30 degrees pa, 4.000 pd, 16/32 pitch, 4.063-4.058 major dia, 3.875-3.864 minor dia; ends counterbored and
grooved
Material:
Steel
Material Specification:
Astm-a513 assn standard single material response or astm-a519 assn standard single material response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli