

View Online at <https://aerobasegroup.com/nsn/3040-00-454-5086>

**First End Style:**

Woodruff keyway and cross drilled

**End Similarity:**

Not identical

**Second End Style:**

Woodruff keyway and cross drilled

**Overall Length:**

6.328 inches

**First End Keyway Width:**

Between 0.1240 inches and 0.1255 inches

**First End External Keyway Length:**

Between 0.760 inches and 0.768 inches

**First End Distance From Keyway Center To End:**

0.875 inches

**First End Diameter:**

Between 0.7475 inches and 0.7490 inches

**First End Hole Diameter:**

Between 0.1406 inches and 0.1562 inches

**First End Distance From Hole Center To End:**

0.188 inches

**Second End Keyway Width:**

Between 0.1240 inches and 0.1255 inches

**Second End External Keyway Length:**

Between 0.760 inches and 0.768 inches

**Second End Distance From Keyway Center To End:**

0.891 inches

**Second End Diameter:**

Between 0.7475 inches and 0.7490 inches

**Second End Hole Diameter:**

Between 0.1406 inches and 0.1562 inches

**Second End Distance From Hole Center To End:**

0.187 inches

**Material:**

Steel comp 1015 or steel comp 1016 or steel comp 1017

**Material Specification:**

Qq-s-633 federal specification single material response

**Fsc Application Data:**

Vehicular steering control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A23200