

View Online at <https://aerobasegroup.com/nsn/3040-00-491-3602>

First End Style:

Unthreaded cross drilled

End Similarity:

Not identical

Second End Style:

Woodruff keyway and circular grooved

Second End Groove Width:

Between 0.0390 inches and 0.0420 inches

Second End Groove Diameter:

Between 0.5810 inches and 0.5910 inches

Overall Length:

8.375 inches

First End Hole Diameter:

0.2660 inches

First End Distance From Hole Center To End:

0.375 inches

Second End Distance From End To Groove:

0.094 inches

Second End Keyway Width:

Between 0.1240 inches and 0.1255 inches

Second End External Keyway Length:

Between 0.500 inches and 0.518 inches

Second End Distance From Keyway Center To End:

1.437 inches

Step Quantity:

3

Largest Step Diameter:

Between 0.620 inches and 0.622 inches

Surface Finish:

125.0 microinches

Special Features:

Ka magnetic permeability shall be less than 1.2 before fabrication and not greater than 2.0 after fabrication as measured in a 200 oersted field by a permeability indicator specified in military specification mil-i-17214

Material:

Steel comp 316

Reference Number Differentiating Characteristics:

As differentiated by special features

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A23200