

View Online at <https://aerobasegroup.com/nsn/3040-00-502-1312>

Radius:

0.120 inches

Outside Diameter:

1.499 inches

Thickness:

0.380 inches

Bore Diameter:

0.8750 inches

Securing Hole Quantity:

1

Securing Hole Type And Location:

Taper pin pilot single hole

Surface Finish And Location:

63 microinches largest outside periphery

Material:

Steel, qq-s-631-canceled and steel, qq-t-830, comp 1022-canceled and steel, qq-s-634, comp 1018 through 1025

Material:

Steel comp 1008 or steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1020 or steel comp 1023 or steel comp 1025 or steel comp 1026 or steel comp 1029 or steel comp 1030 or steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1040 or steel comp 1541 or steel comp 1042 or steel comp 1043 or steel comp 1045 or steel comp 1046 or steel comp 1548 or steel comp 1049 or steel comp 1050 or steel comp 1060 or steel comp 1080 or steel comp 1090 or steel comp 1095 and steel, qq-t-830, comp 1022-canceled and steel, qq-s-634, comp 1018 through 1025

Material Specification:

Qq-s-631-canceled federal specification 1st material response

Surface Treatment:

Phosphate manganese and phosphate zinc

Style Designator:

Round w/ single edge

Surface Treatment:

Phosphate, mil-p-16232, type m, class 2 and phosphate, mil-p-16232, type z, class 1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A231a0