NSN 3040-00-506-8536

Shouldered Shaft - Page 1 of 2



view Online at https://aerobasegroup.com/hsh/3040-00-506-6556
First End Style:
Flat keyway
End Similarity:
Not identical
Second End Style:
Two flat keyways
Overall Length:
18.750 inches
First End Keyway Width:
Between 0.3735 inches and 0.3755 inches
First End External Keyway Length:
1.375 inches
First End Keyway Depth:
0.209 inches
First End Diameter:
Between 1.4990 inches and 1.5000 inches
Second End Keyway Width:
Between 0.3735 inches and 0.3755 inches
Second End External Keyway Length:
1.281 inches
Second End Keyway Depth:
Between 0.187 inches and 0.192 inches
Second End Distance From Keyway Center To End:
14.020 inches
Second End Diameter:
Between 1.7716 inches and 1.7719 inches
Second End Distance Between Keyway Centers:
12.314 inches
Second End Angle Between Keyways:
360.0 degrees
Step Quantity:
2
Largest Step Diameter:
1.771 inches
Surface Finish:
40.0 microinches
Special Features:
First end drilled, 0.453 in. Dia, 1.500 in. Dp, tap 1/2-20unc-2b 1.000 in. Dp; second end cir grooved, 11.033 in. Groove w, 1.750 in. Groove
dia, 2.342 in. Distance from end to groove
Material:
Steel comp 4140
Material Specification:

Mil-s-5626 military specification single material response

NSN 3040-00-506-8536

Shouldered Shaft - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A23200	

Shelf Life:

Mil-std (military Standard):

Mil-s-5626 spec.