## NSN 3040-00-512-9223

Straight Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-512-9223

First End Style:

Two woodruff keyways and cross drilled hole

**End Similarity:** 

Not identical

Second End Style:

Two woodruff keyways and cross drilled hole

**Overall Length:** 

11.000 inches

First End Keyway Width:

0.1880 inches

First End External Keyway Length:

1.250 inches

First End Distance From Keyway Center To End:

1.000 inches

First End Diameter:

Between 1.9970 inches and 2.0000 inches

First End Hole Diameter:

0.1250 inches

First End Distance From Hole Center To End:

1.000 inches

Err Default:

Err default

First End Angle Between Keyways:

180.0 degrees

**Second End Keyway Width:** 

0.1880 inches

Second End External Keyway Length:

1.250 inches

Second End Distance From Keyway Center To End:

1.000 inches

**Second End Diameter:** 

Between 1.9970 inches and 2.0000 inches

**Second End Hole Diameter:** 

0.1880 inches

**Second End Distance From Hole Center To End:** 

1.000 inches

Second End Distance Between Keyway Centers:

Any acceptable

Second End Angle Between Keyways:

180.0 degrees

**Special Features:** 

First end partial bore 10.250 in. Dp; first end int thd 0.375 in. Lg

## NSN 3040-00-512-9223

Straight Shaft - Page 2 of 2

spec.



Material:
Steel comp 1113 or steel comp 1116 or steel comp 1117
Material Specification:
Qq-s-633 military specification all material responses
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A23200
Mil-std (military Standard):