NSN 3040-00-513-5791

Manual Control Lever - Page 1 of 1

A524v0



View Online at https://aerobasegroup.com/nsn/3040-00-513-5791

End Application:
2320-00-835-8344
Special Features:
Bronze casting, irregular shape, forked end, 0.656 in. W, 0.281 in. W slot, 2 holes 0.257 in. Dia, 6.406 in. Lg o/a \sim 0.656 in. W, 0.281 in. W slot, 2 holes 0.257 in. Dia, 6.406 in. Lg o/a \sim 0.656 in. W, 0.281 in. W slot, 2 holes 0.257 in. Dia, 6.406 in. Lg o/a \sim 0.656 in. W, 0.281 in. W slot, 2 holes 0.257 in. Dia, 6.406 in. Lg o/a \sim 0.656 in. W, 0.281 in. W slot, 2 holes 0.257 in. Dia, 6.406 in. Lg o/a \sim 0.656 in. W, 0.281 in. W slot, 2 holes 0.257 in. Dia, 6.406 in. Lg o/a \sim 0.656 in. W, 0.281 in. W slot, 2 holes 0.257 in. Dia, 6.406 in. Lg o/a \sim 0.656 in. W, 0.281 in. W slot, 2 holes 0.257 in. Dia, 6.406 in. Lg o/a \sim 0.656 in. W slot, 2 holes 0.257 in. Dia, 6.406 in. Lg o/a \sim 0.656 in. W slot, 2 holes 0.257 in. Dia, 6.406 in. Lg o/a \sim 0.656 in. W slot, 2 holes 0.257 in. Dia, 6.406 in. Lg o/a \sim 0.656 in. W slot, 2 holes 0.257 in. Dia, 6.406 in. Lg o/a \sim 0.656 in. W slot, 2 holes 0.257 in. Dia, 6.406 in. Lg o/a \sim 0.656 in. W slot, 2 holes 0.257 in. Dia, 6.406 in. Lg o/a \sim 0.656 in. W slot, 2 holes 0.257 in. Dia, 6.406 in. Lg o/a \sim 0.656 in. W slot, 2 holes 0.257 in. Dia, 6.406 in. Lg o/a \sim 0.656 in. W slot, 2 holes 0.257 in. Dia, 6.406 in
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: