## NSN 3040-00-517-5167

Flexible Shaft Assembly - Page 1 of 2



Tiexible Ghalt /165embly Tage Tot 2
View Online at https://aerobasegroup.com/nsn/3040-00-517-5167
Thread Class:
3a first end
Thread Direction:
Right-hand both ends
Thread Length:
0.438 inches both ends
Overall Length:
60.875 inches
Tip Length:
0.750 inches both ends
Core Material:
Steel
Screw Thread Series Designator:
Uns second end
Core Diameter:
0.187 inches
Thread Location:
External first end
End Type:
Round, slotted external first end
Width Across Flats:
1.000 inches second end
End Connection Type:
Threaded internal second end
Setscrew:
Not included both ends
Casing Material:
Steel
Wrenching Facility Type:
Hexagon both ends
Bearing Type:
Ball both ends
Cross Section Size And Location:
0.313 inches diameter second end
Machined Feature Size:

 $0.047\ \text{in.}\ \text{W}$  by  $0.312\ \text{in.}\ \text{Lg}$  slot, first end

**Casing Surface Treatment:** 

Galvanized

**Casing Length Between Ferrules:** 

60.000 inches

**Casing Outside Diameter:** 

0.438 inches

## **NSN 3040-00-517-5167**Flexible Shaft Assembly - Page 2 of 2



Swivel End:
Not provided both ends
Enddiameter:
1.156 inches second end
Lubrication Fitting:
Not provided both ends
Corelength:
60.406 inches
Core Rotation Direction:
Clockwise
Core Removability:
Removable
Minimum Operating Radius:
6.000 inches
Special Features:
Rd permanent keyed drive end on second end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T246-e