

View Online at <https://aerobasegroup.com/nsn/3040-00-517-5173>

Thread Class:

2a both ends

Thread Direction:

Right-hand both ends

Overall Length:

33.125 inches

Flange Thickness:

0.063 inches and 0.313 inches both ends

Thread Depth:

0.375 inches and 0.438 inches both ends

Tip Length:

1.188 inches and 2.063 inches both ends

Shank Outside Diameter:

0.434 inches both ends

Shoulder Outside Diameter:

0.750 inches and 0.813 inches both ends

Core Material:

Steel

Screw Thread Series Designator:

Uns both ends

Core Diameter:

0.156 inches

Thread Location:

Internal both ends

End Type:

Round keyed both ends

Width Across Flats:

0.875 inches both ends

End Connection Type:

Union ferrule both ends

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Knurled surface both ends

Cross Section Size And Location:

0.186 inches diameter both ends

Machined Feature Size:

0.219 in.W 0.431 in.Lg slotted

Torsional Deflection Rating:

6 in.

Casing Surface Treatment:

Zinc coated

Casing Length Between Ferrules:

31.500 inches

Casing Outside Diameter:

0.438 inches

Swivel End:

Not provided both ends

Enddiameter:

1.000 inches both ends

Lubrication Fitting:

Not provided both ends

Corelength:

33.125 inches

Core Rotation Direction:

Counterclockwise

Core Removability:

Removable

Minimum Operating Radius:

6.000 inches

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T246-e