NSN 3040-00-517-5174

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-517-5174

Thread Class:
2a or 2 second end
Thread Direction:
Right-hand both ends
Thread Length:
0.250 inches both ends
Overall Length:
42.031 inches
Wrenching Facility Outside Diameter:
0.750 inches second end
Tip Length:
0.875 inches first end
Shank Outside Diameter:
0.500 inches both ends
Core Material:
Steel
Screw Thread Series Designator:
Uns first end
Core Diameter:
0.150 inches
Thread Location:
Internal first end
End Type:
Square male second end
End Connection Type:
Threaded internal first end
Setscrew:
Not included both ends
Casing Material:
Steel
Wrenching Facility Type:
Knurled surface both ends
Cross Section Size And Location:
0.187 inches diameter first end
Casing Surface Treatment:
Zinc coated
Casing Length Between Ferrules:
42.000 inches
Casing Outside Diameter:
0.445 inches
Swivel End:
Not provided both ends

NSN 3040-00-517-5174

Flexible Shaft Assembly - Page 2 of 2



Enddiameter:

0.875 inches second end

Lubrication Fitting:

Not provided both ends

Corelength:

43.031 inches

Core Rotation Direction:

Clockwise

Core Removability:

Removable

Minimum Operating Radius:

6.000 inches

Special Features:

Rd permanent keyed drive end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T246-e