

View Online at <https://aerobasegroup.com/nsn/3040-00-517-5179>

Thread Class:

2a both ends

Thread Direction:

Right-hand both ends

Thread Length:

0.250 inches and 0.375 inches both ends

Overall Length:

24.875 inches

Wrenching Facility Outside Diameter:

0.936 inches both ends

Tip Length:

0.250 inches and 0.625 inches both ends

Shank Outside Diameter:

0.344 inches both ends

Core Material:

Steel

Screw Thread Series Designator:

Uns both ends

Core Diameter:

0.130 inches

Thread Location:

Internal first end

End Type:

Square male second end

Width Across Flats:

0.813 inches both ends

End Connection Type:

Threaded external both ends

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Hexagon both ends

Cross Section Size And Location:

0.203 inches diameter first end

Casing Surface Treatment:

Galvanized

Casing Length Between Ferrules:

24.000 inches

Casing Outside Diameter:

0.243 inches

Swivel End:

Not provided both ends

Enddiameter:

0.875 inches and 1.000 inches both ends

Lubrication Fitting:

Not provided both ends

Corelength:

24.875 inches

Core Rotation Direction:

Clockwise

Core Removability:

Removable

Minimum Operating Radius:

6.000 inches

Special Features:

Rd permanent keyed drive end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-e