

NSN 3040-00-517-5182 Flexible Shaft Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3040-00-517-5182 **Thread Class:** 2a first end **Thread Direction:** Right-hand both ends

0.250 inches both ends **Overall Length:**

38.031 inches

Thread Length:

Wrenching Facility Outside Diameter:

0.750 inches second end

Tip Length:

0.875 inches first end

Shank Outside Diameter:

0.500 inches both ends

Core Material:

Steel

Screw Thread Series Designator:

Uns first end

Core Diameter:

0.150 inches

Thread Location:

Internal first end

End Type:

Square male second end

End Connection Type:

Union ferrule first end

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Knurled surface both ends

Cross Section Size And Location:

0.187 inches diameter first end

Casing Surface Treatment:

Zinc coated

Casing Length Between Ferrules:

37.000 inches

Casing Outside Diameter:

0.445 inches

Swivel End:

Not provided both ends

NSN 3040-00-517-5182Flexible Shaft Assembly - Page 2 of 2



Enddiameter:
0.875 inches second end
Lubrication Fitting:
Not provided both ends
Corelength:
38.031 inches
Core Rotation Direction:
Clockwise
Core Removability:
Removable
Minimum Operating Radius:
6.000 inches
Special Features:
Rd permanent keyed drive end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T246-e