

View Online at <https://aerobasegroup.com/nsn/3040-00-517-5196>

Thread Class:

2a both ends

Thread Direction:

Right-hand both ends

Thread Length:

1.000 inches both ends

Overall Length:

24.031 inches

Wrenching Facility Outside Diameter:

0.750 inches and 1.000 inches both ends

Tip Length:

0.156 inches and 0.875 inches both ends

Shank Outside Diameter:

0.500 inches both ends

Core Material:

Steel

Screw Thread Series Designator:

Unef both ends

Core Diameter:

0.150 inches

Thread Location:

Internal first end

End Type:

Square male second end

Width Across Flats:

1.000 inches both ends

End Connection Type:

Threaded external both ends

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Knurled surface both ends

Cross Section Size And Location:

0.187 inches diameter first end

Casing Surface Treatment:

Zinc coated

Casing Length Between Ferrules:

24.000 inches

Casing Outside Diameter:

0.445 inches

Swivel End:

Not provided both ends

Enddiameter:

0.875 inches and 1.000 inches both ends

Lubrication Fitting:

Not provided both ends

Corelength:

25.031 inches

Core Rotation Direction:

Clockwise

Core Removability:

Removable

Minimum Operating Radius:

6.000 inches

Special Features:

Rd permanent keyed drive end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-e